

07/27/00
JC840 U.S. PTO

A
JC813 U.S. PTO
09/627139
07/27/00

Case Docket No. US000179
THE COMMISSIONER OF PATENTS AND TRADEMARKS, Washington, D.C. 20231

Enclosed for filing is the patent application of Inventor(s):

J. DAVID SCHAFFER, KWOK PUN LEE, SRINIVAS GUTTA

For: THREE-WAY MEDIA RECOMMENDATION METHOD AND SYSTEM

ENCLOSED ARE:

- ☒ Associate Power of Attorney;
- ☒ Information Disclosure Statement, Form PTO-1449 and copies of documents listed therein;
- ☐ Preliminary Amendment;
- ☒ Specification (34 Pages of Specification, Claims, & Abstract);
- ☒ Declaration and Power of Attorney:
(2 Pages of a ☒ fully executed ☐ unsigned Declaration);
- ☒ Drawing (8 sheets of ☐ informal ☐ formal sheets);
- ☐ Certified copy of application Serial No. ;
- ☒ Other: Authorization Pursuant to 37 CFR 1.136;
- ☒ Assignment to Philips Electronics North America Corporation

FEE COMPUTATION

CLAIMS AS FILED				
FOR	NUMBER FILED	NUMBER EXTRA	RATE	BASIC FEE - 690.00
Total Claims	29 - 20 =	9	X \$18 =	162.00
Independent Claims	6 - 3 =	3	X \$78 =	234.00
Multiple Dependent Claims, if any			\$260 =	0.00
TOTAL FILING FEE				= \$1,086.00

Please charge Deposit Account No. 14-1270 in the amount of the total filing fee indicated above, plus any deficiencies. The Commissioner is also hereby authorized to charge any other fees which may be required, except the issue fee, or credit any overpayment to Account No. 14-1270.

☐ Amend the specification by inserting before the first line the sentence: --This is a continuation-in-part of application Serial No. , filed .--.

CERTIFICATE OF EXPRESS MAILING

Express Mail Mailing Label No. EL458218016

Date of Deposit July 27, 2000

I hereby certify that this paper and/or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Noemi Chapa
Printed Name

Noemi Chapa
Signature

Gregory L. Thorne
Gregory L. Thorne, Reg. No. 39,398
Attorney
(914) 333-9665
U.S. Philips Corporation
580 White Plains Road
Tarrytown, New York 10591
F:\WPDOCS\TH\mw25thk0.nc0.doc

THREE-WAY MEDIA RECOMMENDATION METHOD AND SYSTEM

S P E C I F I C A T I O N

BACKGROUND OF THE INVENTION

5 The present invention relates to systems that employ electronic program guides (EPGs) to assist media users in managing a large number of media-content choices, for example, television programming, chatrooms, on-demand video
10 media files, audio, etc. More specifically, the invention relates to such systems that provide "intelligence", such as an ability to suggest choices and an ability to take actions, for example to record a program, on the user's behalf based on the user's preferences.

15 A common element among conventional Electronic Program Guide (EPG) systems is their ability to display listings of programs for many available channels. The listings may be generated locally and displayed interactively. The listings are commonly arranged in a grid, with each row representing
20 a particular broadcast or cable channel, such as ABC, PBS, or ESPN and each column of the grid representing a particular time slot, such as 4:00 p.m. to 4:30 p.m. Multiple rows and multiple columns can be displayed on the screen simultaneously. The various scheduled programs or

shows are arranged within the rows and columns, indicating the channels and times at which they can be found. The grid can be scrolled vertically so that a viewer can scan through different channels within a given interval of time. The grid may also be scrolled horizontally (panned) to change the time interval displayed.

Data regarding available programs may be received by a cable system or telephone line as a set of data records.

Each available program may have a single corresponding data record containing information about the program such as its channel, its starting and ending times, its title, names of starring actors, whether closed-captioning and stereo are available, and perhaps a brief description of the program.

It is not difficult to format a grid such as described above from these types of data records. The data spanning a period (e.g., two weeks) are typically formatted once at the server (e.g., the cable system's head-end) and broadcast repeatedly and continuously to the homes served by the cable system. Alternatively, the data may be downloaded via phone line, or other network, either on-demand or on a predetermined schedule.

An EPG system can run on a device with a user interface (hereinafter a "user interface device"), which can be a set-top box (STB), a general purpose computer, an embedded

system, a controller within the television, or the server of a communications network or Internet server. The user interface device is connected to the TV to generate displays and receive input from the user. When scrolling to a new column or row, the user interface device may retrieve appropriate information from a stored database (in the user interface device or elsewhere) regarding the programming information that needs to be presented for the new row or column. For instance, when scrolling to a new column, programs falling within a new time slot need to be displayed.

Electronic program guides (EPGs) promise to make more manageable, the task of choosing from among the myriad television and other media viewing choices. An interactive application of EPGs builds a user-preference database and uses the preference data to make suggestions, filter current or future programming information to simplify the job of choosing, or even make choices on behalf of the user. For example, the system could record a program without a specific request from the user or highlight choices that it recommends.

A first type of device for building the preference database is a passive one from the standpoint of the user. The user merely makes choices in the normal fashion from raw

EPG data and the system gradually builds a personal preference database by extracting a model of the user's behavior from the choices. It then uses the model to make predictions about what the user would prefer to watch in the future. This extraction process can follow simple algorithms, such as identifying apparent favorites by detecting repeated requests for the same item, or it can be a sophisticated machine-learning process such as a decision-tree technique with a large number of inputs (degrees of freedom). Such models, generally speaking, look for patterns in the user's interaction behavior (i.e., interaction with the user-interface (UI) for making selections).

One straightforward and fairly robust technique for extracting useful information from the user's pattern of watching is to generate a table of feature-value counts. An example of a feature is the "time of day" and a corresponding value could be "morning." When a choice is made, the counts of the feature-values characterizing that choice are incremented. Usually, a given choice will have many feature-values. A set of negative choices may also be generated by selecting a subset of shows (optionally, at the same time) from which the choice was discriminated. Their respective feature-value counts will be decremented (or a

count for shows not watched incremented). These data are sent to a Bayesian predictor which uses the counts as weights to feature-counts characterizing candidates to predict the probability that a candidate will be preferred by a user. This type of profiling mechanism is described in US Patent Application Ser. No. 09/498,271, filed 2/4/2000 for BAYESIAN TV SHOW RECOMMENDER, the entirety of which is hereby incorporated by reference as if fully set forth herein. A rule-based recommender in this same class of systems, which build profiles passively from observations of user behavior, is also described in the PCT application, WO 99/01984 published 1/14/99 for INTELLIGENT ELECTRONIC PROGRAM GUIDE.

Another example of the first type is MbTV, a system that learns viewers' television watching preferences by monitoring their viewing patterns. MbTV operates transparently and builds a profile of a viewer's tastes. This profile is used to provide services, for example, recommending television programs the viewer might be interested in watching. MbTV learns about each of its viewer's tastes and uses what it learns to recommend upcoming programs. MbTV can help viewers schedule their television watching time by alerting them to desirable upcoming programs, and with the addition of a storage

device, automatically record these programs when the viewer is absent.

MbTV has a Preference Determination Engine and a Storage Management Engine. These are used to facilitate time-shifted television. MbTV can automatically record, rather than simply suggest, desirable programming. MbTV's Storage Management Engine tries to insure that the storage device has the optimal contents. This process involves tracking which recorded programs have been viewed (completely or partially), and which are ignored. Viewers can "lock" recorded programs for future viewing in order to prevent deletion. The ways in which viewers handle program suggestions or recorded content provides additional feedback to MbTV's preference engine which uses this information to refine future decisions.

MbTV will reserve a portion of the recording space to represent each "constituent interest." These "interests" may translate into different family members or could represent different taste categories. Though MbTV does not require user intervention, it is customizable by those that want to fine-tune its capabilities. Viewers can influence the "storage budget" for different types of programs. For example, a viewer might indicate that, though the children watch the majority of television in a household, no more

than 25% of the recording space should be consumed by children's programs.

A second type of device is more active. It permits the user to specify likes or dislikes by grading features.

5 These can be scoring feature-value pairs (a weight for the feature plus a value; e.g., weight = importance of feature and value the preferred or disfavored value) or some other rule-specification such as favorite programs, combinations of feature-value pairs like "I like documentaries, but not
10 on Thursday which is the night when the gang comes over." For example, the user can indicate, through a user interface, that dramas and action movies are favored and that certain actors are disfavored. These criteria can then be applied to predict which, from among a set of programs,
15 would be preferred by the user.

As an example of the second type of system, one EP application (EP 0854645A2), describes a system that enables a user to enter generic preferences such as a preferred program category, for example, sitcom, dramatic series, old
20 movies, etc. The application also describes preference templates in which preference profiles can be selected, for example, one for children aged 10-12, another for teenage girls, another for airplane hobbyists, etc.

A third type of system allows users to rank programs in

some fashion. For example, currently, TIVO® permits user's
to give a show up to three thumbs up or up to three thumbs
down. This information is similar in some ways to the
second type of system, except that it permits a finer degree
of resolution to the weighting given to the feature-value
pairs that can be achieved and similar to the first type
except the expression of user taste in this context is more
explicit. (Note, this is not an admission that the Bayesian
technology discussed in US Patent Application Ser. No.
09/498,271 combined with user-ranking, as in the third type
of system, is in the prior art.)

A PCT application (WO 97/4924 entitled System and
Method for Using Television Schedule Information) is an
example of the third type. It describes a system in which a
user can navigate through an electronic program guide
displayed in the usual grid fashion and select various
programs. At each point, he/she may be doing any of various
described tasks, including, selecting a program for
recording or viewing, scheduling a reminder to watch a
program, and selecting a program to designate as a favorite.
Designating a program as a favorite is for the purpose,
presumably, to implement a fixed rule such as: "Always
display the option of watching this show" or to implement a
recurring reminder. The purpose of designating favorites is

not clearly described in the application. However, more importantly, for purposes of creating a preference database, when the user selects a program to designate as a favorite, she/he may be provided with the option of indicating the reason it is a favorite. The reason is indicated in the same fashion as other explicit criteria: by defining generic preferences.

The first type of system has the advantage of being easier on the user since the user does not have to provide any explicit data. The user need merely interact with the system. For any of the various machine-learning or predictive methods to be effective, a substantial history of interaction must be available to build a useful preference database. The second and third types have the advantage of providing explicit preference information. The second is reliable, but not perfect as a user may have a hard time abstracting his own preferences to the point of being able to decide which criteria are good discriminators and what weight to give them. The third does not burden the user and probably provides the best quality of information, but can be a burden to generate and still may not contain all the information that can be obtained with the second and also may require information on many shows like the first.

SUMMARY OF THE INVENTION

Briefly, an electronic programming guide (EPG) system employs a preference engine and processing system that combines explicit rule profile, history profile, and feedback profile data to generate new predictions.

Television shows are presumed to be indexed by many features. These features are extracted and counted for TV shows watched (implicit profile), and for TV shows rated by the viewer (feedback profile). These profiles are straightforward to combine with suitably greater weight being given to the feedback information. In addition, explicit profiles can make recommendations that stand alone or may be used to modify recommendations arising from either of the other two sources. The modifications may take the form of additive or multiplicative changes to the existing recommendations or some other suitable mathematical form.

The invention will be described in connection with certain preferred embodiments, with reference to the following illustrative figures so that it may be more fully understood.

With reference to the figures, it is stressed that the particulars shown are by way of example and for purposes of illustrative discussion of the preferred embodiments of the present invention only, and are presented in the cause of

providing what is believed to be the most useful and readily understood description of the principles and conceptual aspects of the invention. In this regard, no attempt is made to show structural details of the invention in more detail than is necessary for a fundamental understanding of the invention, the description taken with the drawings making apparent to those skilled in the art how the several forms of the invention may be embodied in practice.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a television/monitor displaying an EPG, with a computer to generate the EPG display, and an interaction interface suitable for use with embodiments of the invention.

FIG. 2 shows a remote control suitable for use with UI embodiments of the invention.

FIG. 3 shows an EPG display suitable for use with UI embodiments of the invention.

FIG. 4 shows a layout of physical components through which various embodiments of the invention may be realized.

FIG. 5 illustrates the flow of data in feedback-based profilers according to an embodiment of the invention.

FIG. 6 illustrates the flow of data in view-history-based profilers according to an embodiment of the invention.

FIG. 7 illustrates the flow of data in explicit-based profilers according to an embodiment of the invention.

FIG. 8 illustrates the combination of three different types of profile data to provide a combined recommendation process according to an embodiment of the invention.

FIG. 9 illustrates the combination of three different types of profile data to provide a combined recommendation process according to another embodiment of the invention.

FIG. 10 illustrates the combination of three different types of profile data to provide a combined recommendation process according to still another embodiment of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Figs. 1-4 the invention relates to the environment of electronic program guides (EPGs). In the context of televisions, EPG is applied loosely to various features that can be delivered using a database of program information. The program information may include titles and various descriptive information such as a narrative summary, various keywords categorizing the content, etc. In an embodiment, a computer 240 sends program information to a television 230. The program information can be shown to the user in the form of a time-grid display 170 similar to the

format commonly used for existing cable television channel guides. In the time-grid display 170, various programs are shown such as indicated by bars at 120, 125, 130, 135, and 140. The length of each bar (120-140) indicates a
5 respective program's duration and the start and end points of each bar indicate the start and end times, respectively, of each respective program. A description window 165 provides detailed information about a currently selected program. The currently selected program, Program 7 at 125,
10 is indicated by, for example, highlighting a colored border 137 around the currently selected program item. Various devices may be used to select programs, such as cursor keys 215 on remote control 210.

Referring now also to FIG. 4, the computer 240 may be
15 equipped to receive the video signal 270 and control the channel-changing function, and to allow a user to select channels through a tuner 245 linked to the computer 240 rather than through the television's tuner 230. The user can then select the program to be viewed by highlighting a
20 desired selection from the displayed program schedule using the remote control 210 to control the computer. The computer 240 has a data link 260 through which it can receive updated program schedule data. This could be a telephone line connectable to an Internet service provider

or some other suitable data connection. The computer 240 has a mass storage device 235, for example a hard disk, to store program schedule information, program applications and upgrades, and other information. Information about the user's preferences and other data can be uploaded into the computer 240 via removable media such as a memory card or disk 220.

Note that many substitutions are possible in the above example hardware environment and all can be used in connection with the invention. The mass storage can be replaced by volatile memory or non-volatile memory. The data can be stored locally or remotely. In fact, the entire computer 240 could be replaced with a server operating offsite through a link. Rather than using a remote control to send commands to the computer 240 through an infrared port 215, the controller could send commands through a data channel 260 which could be separate from, or the same as, the physical channel carrying the video. The video 270 or other content can be carried by a cable, RF, or any other broadband physical channel or obtained from a mass storage or removable storage medium. It could be carried by a switched physical channel such as a phone line or a virtually switched channel such as ATM or other network suitable for synchronous data communication. Content could

be asynchronous and tolerant of dropouts so that present-day
IP networks could be used. Further, the content of the line
through which programming content is received could be
audio, chat conversation data, web sites, or any other kind
of content for which a variety of selections are possible.

The program guide data can be received through channels
other than the separate data link 260. For example, program
guide information can be received through the same physical
channel as the video or other content. It could even be

provided through removable data storage media such as memory
card or disk 220. The remote control 210 can be replaced by
a keyboard, voice command interface, 3D-mouse, joystick, or
any other suitable input device. Selections can be made by
moving a highlighting indicator, identifying a selection

symbolically (e.g., by a name or number), or making
selections in batch form through a data transmission or via
removable media. In the latter case, one or more selections
may be stored in some form and transmitted to the computer
240, bypassing the display 170 altogether. For example,

batch data could come from a portable storage device (e.g.
a personal digital assistant, memory card, or smart card).
Such a device could have many preferences stored on it for
use in various environments so as to customize the computer
equipment to be used.

Referring now to FIG. 5, in a system of the third type in which the user provides feedback to rank a choice as liked or disliked and optionally to a degree. For example, the Tivo® system uses 1, 2, and 3, or a score from 1-7 with 4 being neutral. A user interface (UI) 300 is used to list programs and accept the feedback information.

Alternatively, the UI 300 may be a simple prompt that requests the user to give feedback on a program when the program either ends or when the user switches away from the program. Preferably, the prompt-type would be subject to a preference set that would allow the user to override the prompting in some or all situations if desired.

The information generated by each instance of the feedback UI 300 is one or more choices (shows, if it is a television database) 440 with a score associated with the choice. This is used to charge a feedback history file 305 which can contain a large number of such entries. The feedback data 445 may then be applied to a profiler 350. Alternatively the data can be stored in reduced form by reducing it in a profiler 350 first and then storing in a feedback profile database 325. The reduction may be a set of feature-value pairs 450, each with a ranking as described in 09/498,271, filed 2/4/2000 for BAYESIAN TV SHOW RECOMMENDER. A given choice may give rise to a number (M)

feature value pairs 450 with corresponding scores.

Preferably, the user rates programs that are both liked and disliked so that both positive and negative feedback are obtained. If only positive feedback is acquired, say because feedback is only provided for programs selected for viewing, then the negative factors may not populate the database. This can be improved then, by having the system generate a set of negative choices by selecting a subset of shows available at the same the choice was made.

Preferably, as stated, the user provides a balance of positive and negative feedback and the automatic sampling of negative choices is not required. Their respective feature-value counts would be decremented. This data stored over many choices may be stored in the feedback profile 325 database. The entire body of N records 455 is then available when the recommender 400 makes recommendations based on a list of candidates derived from a show database 320. The end result of this process is a filtered or sorted list 460 of choices available from the show database 320.

The recommender may be a Bayesian filter or any other predictor.

Referring to Fig. 6, a very similar process as in Fig. 5 may be used to generate a feature-value pair profile database. This predictor is of the first type described in

the background section. Here, a user's selection of a program choice is inferred to indicate a positive score for a program choice. The result of a given choice by a user is a particular program 465 optionally with an attending score.

5 This result can also include a score which may be inferred from the way the user responded. If the user watched the program to completion, the score may be high and if watched for only a short time, the score could be negative. If the program were watched for a period between these two, the
10 score could be a middle magnitude. Alternatively, a watched program could receive a positive score and a random sample of unwatched programs (optionally, at the same time) a negative score.

The view history database 310 stores the shows and
15 scores. The records 470 are supplied to a profiler 355 which generates feature-value pairs with attending scores 475, which may be stored in an implicit profile database 330. The contents 480 of the implicit profile database 330 are then available to a recommender 420 which combines them
20 with data from current shows 320 to generate recommendations 485.

In the example embodiments of Figs. 5 and 6, we have assumed a Bayesian recommender. It is also possible to use other types of predictive techniques, which would require

the alteration of the intermediate data streams. For example, a decision-tree technique would not generate feature-value pairs but rather search the corpus of choices and scores for the feature that is the best discriminator making that the root of the tree, and then searching for the penultimate discriminators to define branches of the tree, and so on. A neural-net type of model is also another example and its input vector set would simply be the show-score data and the stored data, the weights on its interconnects.

Referring to Fig. 7, an explicit profile 315 is formed by having a user interact with a UI 317 to indicate preferences. As an example, the result may be the explicit indication of feature-value pairs with associated scores 490. In this case, these feature-value pairs may be weighted by the user as well. Thus, a user might be asked to indicate how important the particular feature and/or feature-value pair is in his/her decision-making. The resulting rules may be stored in an explicit profile database 315 which may then be used by a recommender 510, such as Bayesian recommender or any other suitable type. Optionally, the rules 490 may be augmented/modified by combination 415 with external data 425 using collaborative filtering techniques. The result again, as in the previous

embodiments, is a list of show recommendations 515.

The two types of recommendation processes illustrated in Figs. 5 and 6 may be joined at an intermediate step if their input vectors (to the recommender) are the same. For example, if both processes will use Bayesian filtering, the input vectors will be feature-value pairs with attending scores. These may be combined in an arithmetic or weighted sum and then applied directly to a single recommender.

Referring now to Fig. 8, feature value pairs from each of the feedback profile 325 and the implicit profile 330 are applied to a process 370 that weights and sums the two sets of feature-value pair/score vectors. Preferably, the feedback profile data are provided greater weight than the implicit profile data. A combined recommender 365 can then make recommendations 335. These may be used directly to select shows.

In a further embodiment, also illustrated in Fig. 8, the recommendations from combined feedback and implicit profiles are combined with recommendations based on an explicit profile. The explicit profile recommendations 342 are generated in the fashion employed in the embodiment of Fig. 7 and applied to a merge/override process 375 to produce recommendations 340. The recommendations from the previously-discussed combination of implicit and explicit

profiles are also applied to the merge/override process 375.

The merge/override process 375 combines the two sets of recommendations as follows.

Each set of recommendations may be represented as a list of choices with corresponding confidence levels. For example, a high confidence level indicates that the recommender generated a strong indication that the choice would be preferred by the user. The combination of the two sets may be a weighted average, with the explicit recommendations receiving greater weight. Thus, a show whose confidence was 90% in the explicit profile's process and 75% in the combined implicit and feedback profiles' process, may be weight-averaged to produce a value of 85%. Preferably, the merge/override process 375 overrides a weighted average if the two are highly disparate. In such a case, the explicit profile may be favored (i.e., trump the combined implicit and feedback profile recommendations) or the weighting corresponding to the difference to produce much greater emphasis on the explicit as the divergence increases. The

Still referring to Fig. 8, in another embodiment, the feedback UI 300 may display the explicit profile recommendations on its display. For example, if a user just finished watching a show and was prompted for a rating, the

explicit profile's rating of that show could be shown alongside or after the user rated the show. If there were a disparity the user could request to see the rules that generated that result and selectively make corrections.

5 Alternatively, the system could automatically expose those rules that generated the result when there was a threshold disparity between the two ratings. Thus, a conditional link to the explicit profile UI 315 may be generated when the user is in the feedback UI 300.

10 Referring now to Fig. 9, in a mechanism for combining profiles that is similar to that of Fig. 8, the inputs to the profilers are all assumed to be essentially of the same type. For example, all may be feature vectors with scores or all may be rated choices. For example, assume the inputs
15 are feature-value pairs with corresponding ranking. Each may then be combined in a combined weight and sum processor 371. The combined profile data may then be supplied to a combined recommender 365.

20 The weight and sum process could provide various ways of combining the vector sets. For one thing, if there is a head-to-head collision between explicit profile vectors and implicit or feedback profile vectors, one may trump the other or, optionally, the user could be prompted to attempt to resolve the discrepancy. Note that the output of the

weight and sum process 371 could be performed periodically
and the results stored until used for recommendations.

Referring still to Fig. 9, it is possible to use
collaborative filtering techniques at various points in the
processes of Figs. 8 and 9. External user preference data
of all three forms, explicit, implicit, and feedback, can be
combined with similar data synthesized from the data of many
users using known techniques. In the example of Fig. 9 the
combination of explicit profile data with external data is
illustrated but this could be done with any other or all
three classes of user preference data.

Another possible way to combine data where the input
vectors for the explicit recommender are not of the same
form as either of the other two types is to generate show
ratings using the explicit recommender. Then the show
ratings can be fed to the decision tree, neural network, or
other predictor and combined into one body of input vectors
to a single recommender. Alternatively, if for example a
Bayesian recommender were used, the explicit profile
recommendations could be reduced appropriately by a profiler
to yield feature-value rating vectors which can be combined
with those of the implicit and feedback profiles. Then the
combined set can be fed to a single Bayesian recommender.

Referring to Fig. 10, in another embodiment, each type

of profile 325, 330, and 315 is fed to a corresponding recommender 600, 610, and 620. In this embodiment, it is assumed all three types of recommenders have different types of inputs. As discussed with respect to the embodiment of Fig. 8, the different recommendations can still be combined by a single merge override process 630 to make the final recommendations.

It is clear from the above description that the identical techniques of combining disparate profile data may be applied in other contexts than television EPGs. For example, the same techniques could be applied to generate favorites for web-surfing or media forms other than television such as radio broadcasts. Library browsing is another example. One may envision an online library or journal article database where precisely the same techniques may be employed to limit the range of choices. The above system could be used to customize the user interfaces of web sites that provide news articles or sell products, to name a couple of examples.

It will be evident to those skilled in the art that the invention is not limited to the details of the foregoing illustrative embodiments, and that the present invention may be embodied in other specific forms without departing from the spirit or essential attributes thereof. The present

embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description, and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

We claim:

1 1. An automated recommendation system, comprising:
2 a processor connected to receive resource data defining
3 available resources and at least two sets of profile data,
4 each defining user preferences with respect to said
5 resources;

6 each of said sets of profile data being derived from a
7 different class of interaction of said user with a first
8 portion of said resource data and usable to predict a given
9 resource's desirability based on said each of said sets;
10 said processor being adapted to generate a weighted sum
11 of corresponding records from each of said sets to generate
12 a single combined set of profile data.

1 2. A system as in claim 1, wherein said processor is
2 further adapted to generate predictions from said single
3 combined set.

1 3. A system as in claim 2, wherein said processor is
2 connected to control a delivery of resources corresponding
3 to said resource data and responsively to said predictions.

1 4. A system as in claim 1, wherein said processor is
2 connected to control a delivery of resources corresponding
3 to said resource data and responsively to said predictions.

1 10. A method as in claim 9, further comprising the
2 step of generating predictions from said single combined
3 set.

1 11. A method as in claim 10, further comprising the
2 step of controlling a delivery of resources corresponding to
3 said resource data responsively to said predictions.

1 12. A method as in claim 9, further comprising the
2 step of controlling a delivery of resources corresponding to
3 said resource data responsively to said predictions.

1 13. A method as in claim 9, wherein said step of
2 generating includes generating a feedback data set by
3 accepting ratings from a user with respect to a particular
4 resource in said resource data.

1 14. A method as in claim 9, wherein said step of
2 generating includes generating an implicit data set by
3 observing a user's resource use history, whereby said
4 implicit data reflects said user's selections of resources
5 to use.

1 15. A method as in claim 9, wherein said input vectors
2 each include feature-value pairs.

1 16. A method as in claim 9, wherein said step of
2 generating includes generating feature-value pairs and a
3 rating value.

4

24 said sets of profile data further including an implicit
 25 data set derived from machine-observation of a user's
 26 resource use history, whereby said implicit data reflects
 27 said user's selection;

28 said processor being adapted to generate at least two
 29 sets of predictions based on one or a combination of said
 30 sets of profile data, each of said predictions including a
 31 confidence level;

32 said processor being further adapted to combine said
 33 predictions by weight-averaging corresponding ones from each
 34 of said at least two sets .

1 19. A system as in claim 18, wherein said processor is
 2 further adapted to adjust weights of said weight averaging
 3 responsively to a difference between said corresponding
 4 ones.

1 20. A system as in claim 18, wherein said processor is
 2 further adapted to selectively override said weight
 3 averaging responsively to a difference between said
 4 corresponding ones.

1 21. A method of automatically recommending resources,
 2 comprising the steps of:

3 receiving resource data defining available resources
 4 and sets of profile data, each defining user preferences
 5 with respect to said resources;

4 corresponding ones such that a prediction of a one of said
5 sets of predictions is included in said combined set and a
6 prediction of the other of said sets of predictions is
7 excluded.

1 24. A method of combining profile data, comprising the
2 steps of:

```

3         generating first profile data by receiving through a
4         user interface user preferences in the form of expressed
5         generalized preferences corresponding classes of resources;

```

```

6     generating second profile data by receiving user
7 preferences in the form of rating data corresponding to
8 specific resources;

```

9 combining said first and second profile data to produce
10 predictions by one of:

11 applying said first and second profile data to
12 respective prediction engines and combining respective
13 results thereof; and

14 directly combining said first and second profile
15 data to a prediction engine.

1 25. A method as in claim 24, wherein said step of
2 directly combining includes weight averaging corresponding
3 ones of said profile data.

1 26. A method as in claim 24, wherein said step of
2 combining respective results includes selectively weight
3 averaging corresponding ones of said predictions

1 27. A method of modifying a preference profile for
2 making resource-choice recommendations, comprising the steps
3 of:

4 forming a profile based on expressed preferences of a
5 user;

6 presenting at least one resource from a database of
7 available resources;

8 generating at least one suitability prediction
9 responsively to said profile and said at least one resource;

10 selectively accepting data from said user to modify
11 said profile responsively to said step of generating.

1 28. A method as in claim 27, wherein said profile is a
2 database of explicitly-specified rules indicating
3 preferences of said user.

1 29. A method as in claim 27, wherein said step of
2 selectively accepting includes displaying data from said
3 profile on which said suitability prediction is based.

1

ABSTRACT

An electronic programming guide (EPG) system employing a preference engine and processing system that combines explicit rule profile, history profile, and feedback profile data to generate new predictions. Television shows are presumed to be indexed by many features. These features are extracted and counted for TV shows watched (implicit profile), and for TV shows rated by the viewer (feedback profile). These profiles are straightforward to combine with suitably greater weight being given to the feedback information. In addition, explicit profiles can make recommendations that stand alone or may be used to modify recommendations arising from either of the two sources. The modifications may take the form of additive or multiplicative changes to the existing recommendations or some other suitable mathematical form.




Fig. 1




Fig. 2




Fig. 3

004220" 66T/23950




Fig. 4




Fig. 5




Fig. 6




Fig. 7


```

graph TD
    FeedbackUI[Feedback UI 300] --> FeedbackHistory[(Feedback history 305)]
    FeedbackHistory --> Profiler350[Profiler 350]
    Profiler350 --> FeedbackProfile[(Feedback profile 325)]
    FeedbackProfile --> WeightSum[Weight & sum 370]
    
    ExplicitProfileUI[Explicit profile UI 317] --> ExplicitProfile[(Explicit profile 315)]
    ExplicitProfile --> ExplicitRecommender[Explicit recommender 360]
    ExplicitRecommender --> Recommendations342[(Recommendations 342)]
    
    Shows320[(Shows 320)] --> ViewHistory[(View history 310)]
    ViewHistory --> Profiler355[Profiler 355]
    Profiler355 --> ImplicitProfile[(Implicit profile 330)]
    ImplicitProfile --> WeightSum
    
    WeightSum --> CombinedRecommender[Combined recommender 365]
    FeedbackProfile --> CombinedRecommender
    CombinedRecommender --> Recommendations335[(Recommendations 335)]
    
    Recommendations335 --> MergeOverride[Merge override 375]
    Recommendations342 --> MergeOverride
    MergeOverride --> Composite340[(Composite 340)]
    
    FeedbackUI --> Shows320
    ExplicitProfileUI --> Shows320
    Shows320 --> ExplicitProfile
  
```

Fig. 8

Fig. 8




Fig. 9




Fig. 10

DECLARATION and POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **Three-Way Media Recommendation Method and System** the specification of which (check one)
☒ is attached hereto.

☐ was filed on _____ as Application Serial No. _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by the amendment(s) referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulation, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

COUNTRY	APPLICATION NUMBER	DATE OF FILING (DAY, MONTH, YEAR)	PRIORITY CLAIMED UNDER 35 U.S.C. 119

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application (s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35 United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

PRIOR UNITED STATES APPLICATION(S)

APPLICATION SERIAL NUMBER	FILING DATE	STATUS (PATENTED, PENDING, ABANDONED)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.


POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)


Algy Tamoshunas, Reg. No. 27,677


Jack E. Haken, Reg. No. 26,902

SEND CORRESPONDENCE TO: Corporate Patent Counsel; U.S. Philips Corporation; 580 White Plains Road;	DIRECT TELEPHONE CALLS TO: Gregory L. Thorne (914) 333-9665
--	---

Tarrytown, NY 10591

Dated: 2000 - 7 - 25		Inventor's Signature: 		
Full Name of Inventor	Last Name: Schaffer	First Name : J.	Middle Name: David	
Residence & Citizenship	City Wappingers Falls	State or Foreign Country New York	Country of Citizenship United States of America	
Post Office Address	Street 101 Edgehill Drive	City Wappingers Falls	State or Country New York	Zip Code 12590

Dated: 7/19/2000		Inventor's Signature: 		
Full Name of Inventor	Last Name: Lee	First Name : Kwok	Middle Name: Pun	
Residence & Citizenship	City Yorktown Heights	State or Foreign Country New York	Country of Citizenship United States of America	
Post Office Address	Street 1701 Maxwell Drive	City Yorktown Heights	State or Country New York	Zip Code 10598

Dated: 07/17/00		Inventor's Signature: 		
Full Name of Inventor	Last Name: Gutta	First Name : Srinivas	Middle Name:	
Residence & Citizenship	City Buchanan	State or Foreign Country New York	Country of Citizenship India	
Post Office Address	Street 80 Tate Avenue, #2	City Buchanan	State or Country New York	Zip Code 10511